

Product Specifications For 910



Weights

Operating Weight	18102 lb
-------------------------	----------

Buckets

Bucket Capacities	1.3-3.5 m ³ (1.7-4.6 yd ³)
--------------------------	---

Bucket Capacities - General Purpose	1.3-1.9 m ³ (1.7-2.5 yd ³)
--	---

Bucket Capacities - Light Material	2.5-3.5 m ³ (3.3-4.6 yd ³)
---	---

Engine

Maximum Gross Power	110 hp
----------------------------	--------

Rated Net Power - Rated Engine Speed	2200 r/min
---	------------

Maximum Gross Power - Rated Engine Speed	1800 r/min
---	------------

Rated Net Power - SAE J1349	99 hp
------------------------------------	-------

Maximum Gross Power - ISO 14396 (metric)	112 hp
---	--------

Rated Net Power - ISO 9249	98 hp
-----------------------------------	-------

Maximum Gross Torque - SAE J1995	335 ft·lbf
---	------------

Maximum Gross Torque - ISO 14396	332 ft·lbf
---	------------

Maximum Net Torque - SAE J1349	329 ft·lbf
---------------------------------------	------------

Maximum Net Torque - ISO 9249	327 ft·lbf
Displacement	220 in ³
Bore	3.85 in
Stroke	4.72 in
Engine Model	Cat C3.6
Emissions	Engine meets Tier 4 Final/Stage V emission standards.
Note	Net power advertised is the power available at the flywheel plus front drive implement pump when the engine is equipped with fan, air cleaner, muffler and alternator.
Maximum Gross Power - ISO 14396	110 hp

Sustainability

Recyclability	95%
----------------------	-----

Cab

ROPS	ISO 3471:2008
FOPS	ISO 3449:2005
Note (2)	The declared dynamic operator sound pressure levels per ISO 6396:2008*, when the cab is properly installed and maintained, is 77 dB(A).
Note (3)	The labelled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC (as amended by 2005/88/EC) is 103 dB(A).
Note (1)	Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.
Note (4)	*The measurements were conducted with the cab doors and windows closed.

Service Refill Capacities

Cooling System	5.7 gal (US)
Fuel Tank	43.6 gal (US)
Hydraulic System - Including Tank	25.9 gal (US)
Hydraulic Tank	14.5 gal (US)
Transmission	0.8 gal (US)
Note	DEF used in Cat SCR systems must meet the requirements outlined in the International Organization for Standardization (ISO) standard 22241-1.
Axles - Front Center Differential	2 gal (US)
Axles - Rear Center Differential	2 gal (US)
Engine Crankcase	2.6 gal (US)
Diesel Exhaust Fluid (DEF) Tank	4.8 gal (US)

Steering

Maximum Working Pressure - Steering Pump	2683 psi
Steering Articulation Angle - Each Direction	40 °
Steering Cycle Times - Full Left to Full Right - At 2,350 rpm: 90 rpm Steering Wheel Speed	3.2 s
Maximum Flow - Steering Pump	17 gpm
Number of Steering Wheel Turns - Full Left to Full Right or Full Right to Full Left	3.75 turns

Loader Hydraulic System

Hydraulic Cycle Time - Dump, at Maximum Reach	1.4 s
Hydraulic Cycle Time - Total Cycle Time	12.5 s
Maximum Working Pressure - Implement Pump	3408 psi
Relief Pressure - Tilt Cylinder	4931 psi
Hydraulic Cycle Time - Rackback	2.2 s
Relief Pressure - Tilt Cylinder - 3rd Function Maximum Working Pressure	3046 psi
Hydraulic Cycle Time - Raise, Ground Level to Maximum Lift	5.2 s
Maximum Flow - Implement Pump	32 gpm
Relief Pressure - Tilt Cylinder - 4th Function Maximum Working Pressure	3046 psi
Maximum Flow - Implement Pump - 4th Function, Maximum Flow	24 gpm
Maximum Flow - Implement Pump - 3rd Function, Maximum Flow	24 gpm
Hydraulic Cycle Time - Float Down, Maximum Lift to Ground Level	3.7 s

Transmission

Note	*Creeper Control allows speed control from a stand still up to 10 km/h (6.3 mph). The Creeper Control will only work in Range 1.
Forward and Reverse - Speed Range 3	25 mile/h
Forward and Reverse - Speed Range 2*	12.5 mile/h
Forward and Reverse - Speed Range 1*	6.3 mile/h

Tires

Note (2) In certain applications, the loader's productive capabilities may exceed the tire's tonnes-km/h (ton-mph) capabilities.

Standard Size 15.5 R25 L2 XTLA

Other Choices Include 17.5 R25 L2 XTLA; 15.5 R25 L3 XHA2; 17.5 R25 L3 XHA2; 17.5-25 L2/L3 SGL; 17.5-25 L3 HRL D/L-3A; 17.5 R25 L2 Snow

Note (3) Caterpillar recommends that you consult a tire supplier to evaluate all conditions before selecting a tire model.

Note (1) Other tire choices are available. Contact your Cat dealer for details.

Axles

Front Fixed; Locking differential (standard)

Rear Oscillating ± 11 degrees; Locking differential (Standard)